

Technical Data

Sizes	XS	S	M	L	XL
Length (mm)	235±5mm	235±5mm	235±5mm	235±5mm	235±5mm
Palm Width	75±5mm	85±5mm	95±5mm	110±5mm	120±5mm
Thumb L.	52±2mm	54±2mm	57±2mm	59±2mm	65±2mm
Forefinger L.	66±2mm	68±2mm	72±2mm	74±2mm	80±2mm
Middle finger L.	77±2mm	79±2mm	82±2mm	85±2mm	92±2mm
Ring finger L.	68±2mm	71±2mm	75±2mm	77±2mm	82±2mm
Little finger L.	52±2mm	54±2mm	56±2mm	60±2mm	64±2mm
Physical Specification		Vinyl Premium	Synthetic Premium	Nitrile Premium	Latex Premium
	Palm Thickness	Min. 0.08mm	Min. 0.08mm	Min. 0.05mm	Min. 0.08mm
	Finger Thickness	Min. 0.05mm	Min. 0.05mm	Min. 0.05mm	Min. 0.08mm
	Wrist Thickness	Min. 0.06mm	Min. 0.06mm	Min. 0.05mm	Min. 0.08mm
	Tensile Strength Before Aging	Min. 11MPa Avg. 12MPa	Min. 11MPa Avg. 16MPa	Min. 14MPa Avg. 18MPa	Min. 18MPa Avg. 20MPa
	Tensile Strength After Aging	Min. 11MPa Avg. 11MPa	Min. 11MPa Avg. 15MPa	Min. 14MPa Avg. 16MPa	Min. 14MPa Avg. 15MPa
	Elongation Rate Before Aging	Min. 300% Avg. 420%	Min. 300% Avg. 460%	Min. 500% Avg. 580%	Min. 650% Avg. 680%
	Elongation Rate After Aging	Min. 300% Avg. 360%	Min. 300% Avg. 410%	Min. 400% Avg. 470%	Min. 500% Avg. 600%
Packaging Dimensions (mm) & Loading Capabilities (Each product may differ from others)	L x W x H	Method 1 (1000 PCs/CTN)	Method 2 (1500 PCs/CTN)	Method 3 (2000 PCs/CTN)	
	Dispenser	230x125x60mm	240x125x70mm	230x130x78mm	
	Trans. CTN.	315x258x250mm	385x260x255mm	408x268x240mm	
	Capability for 20 GP	1500 CTNs	1170 CTNs	1150 CTNs	
	Capability for 40 GP	3100 CTNs	2400 CTNs	2380 CTNs	
	Capability for 40 HQ	3450 CTNs	2700 CTNs	2600 CTNs	

The information above are for reference only. Specific order shall be confirmed according to regional regulations and customers' requirements.